

Raimond II Tensegrity

RAIMOND PUTS




The Raimond Tensegrity is a floor lamp made from elegant metal, complemented with the sturdy earthiness of wood. Tensegrity is a term that was first described by Buckminster Fuller as an architectural term. It refers to the interconnected wooden structure that uses tension and pressure to keep its shape. The beauty of the Raimond Tensegrity lies not only in its contrasting materials, but also in the trigonometric harmony of both structures. Mathematical perfection times two.

Detailing



Raimond Puts never saw his final design. But, together with Raimond's wife, artist & designer Tis Ernst, Moooi completed the Raimond Tensegrity.

Colours




Stainless steel

Raimond II Tensegrity / Raimond II Tensegrity, R61

Dimensions

61cm | 24"



80cm | 31.5"

Product

WIDTH 61cm | 24"

HEIGHT 80cm | 31.5"

DEPTH 61cm | 24"

DIAMETER 61cm | 24"

WEIGHT NETTO 10kg |
22.05lbs

Packaging

WIDTH 75cm | 29.5"

HEIGHT 75cm | 29.5"

CUBAGE 0.42m³ | 14.9ft³

LENGTH 75cm | 29.5"

WEIGHT 10kg | 22.05lbs

Technical CE / CU

MATERIAL

Stainless Steel Sphere (indoor use, not resistant to marine environments) with PMMA lenses, wooden legs and leather straps

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

162

INPUT VOLTAGE

120-250V

FREQUENCY

50/60

MAX POWER CONSUMPTION

17W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

500cm | 196.9"

SWITCH

In line dimmer switch integrated in power supply housing

COLOUR TEMPERATURE

2523 K

CRI

92

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1134 lm

DIMMING & LIGHTING CONTROL


Dimmer on power cord

See last page for more information about the dimming possibilities.

Raimond II Tensegrity / Raimond II Tensegrity, R89

Dimensions

89cm | 35"



113cm | 44.5"

Product

WIDTH 89cm | 35"

HEIGHT 113cm | 44.5"

DEPTH 89cm | 35"

DIAMETER 89cm | 35"

WEIGHT NETTO 16kg | 35.27lbs

Packaging

WIDTH 104cm | 40.9"

HEIGHT 104cm | 40.9"

CUBAGE 1.12m³ | 39.72ft³

LENGTH 104cm | 40.9"

WEIGHT 16kg | 35.27lbs

Technical CE / CU

MATERIAL

Stainless Steel Sphere (indoor use, not resistant to marine environments) with PMMA lenses, wooden legs and leather straps

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

252

INPUT VOLTAGE

120-250V

FREQUENCY

50/60

MAX POWER CONSUMPTION

26W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

500cm | 196.9"

SWITCH

In line dimmer switch integrated in power supply housing

COLOUR TEMPERATURE

2523 K

CRI

92

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1744 lm

DIMMING & LIGHTING CONTROL

Dimmer on power cord

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

Dimmer on power cord

Compatible models: Raimond II Tensegrity, R61 CE, Raimond II Tensegrity, R61 CU, Raimond II Tensegrity, R89 CE, Raimond II Tensegrity, R89 CU
